

Jonopack SQ T5

Surface Fluorescent Luminaires

Jonopack SQ T5, architectural IP44 linear fluorescent luminaire; features a stylish, clean extruded body profile with opal or reeded lens options. Ideal for staircases, corridors, kitchens, classrooms, toilets etc.



Opal lens



Reeded lens

Features:

- IP44 (resists dirt ingress & splash proof)
- Single T5 high efficiency (HE) or high output (HO) linear fluorescent light sources
- High Frequency (HF) control gear ●●
- Ceiling (surface/suspended or wall mounting)
- Suitable for continuous inline runs
- Quick/easy removable lens
- Corrosion resistant
- 2 x 20mm conduit entry for through wiring

Options:





- High Frequency dimmable version available on request ●●●
- Integral 3hr. maintained emergency (E3) ●●
- Choice of lengths (L)
- Choice of fixing/mounting accessories
- Metallic grey body finish available on request

Material:


- Body: extruded aluminium
- Lens: polycarbonate

Finish:

- Body: white (RAL 9010)
- Lens: opal or reeded



Wire suspension



Wall bracket

Jonopack SQ T5

Lamp type (Not supplied)	Length (L)	Fixing (FC)	Ordering Code			
			Opal lens	Emergency (E3) (integral gear)	Reeded lens	Emergency (E3) (integral gear)
1 x 549mm 14w T5 HE (G5)	600	536	AVR67O.014E		AVR67R.014E	
1 x 849mm 21w T5 HE (G5)	900	696	AVR67O.021E		AVR67R.021E	
1 x 1149mm 28w T5 HE (G5)	1200	916	AVR67O.028E	E3-AVR67O.028E	AVR67R.028E	E3-AVR67R.028E
1 x 1449mm 35w T5 HE (G5)	1500	1200	AVR67O.035E	E3-AVR67O.035E	AVR67R.035E	E3-AVR67R.035E
					AVR67R.024E	
					AVR67R.039E	
					AVR67R.054E	E3-AVR67R.054E
					AVR67R.049E	E3-AVR67R.049E

Accessories

	Ordering Code
Wire suspension set (2 pack)	AVL601
90° wall mounting bracket (2 pack)	AVL608



These luminaires are designed to comply with EN 60598-1 (BS 4533:101) Emergency EN 60598.2.22 (BS 4533:102.22)

