

Hawk, IP65 low energy compact fluorescent wall/ceiling luminaire; vandal resistant for interior or exterior use. Ideal applications include toilets, corridors, stairways & passageways etc.



Black body with prismatic lens

Features:

- IP65 (dust tight & water jet proof)
- Low energy compact fluorescent light source
- High Frequency (HF) control gear ●●
- Wall or ceiling mounting
- Vandal resistant
- Screw on lens
- Removable hinged gear tray
- Besa box provision
- 2 x 20mm conduit entry for side wiring

Options:



- Integral 3hr. maintained emergency (E3) ●●
- Integral D-tect occupancy/light sensor (see data sheet M3/102) ●●●●
- Integral photocell (for dawn to dusk operation) Suffix ordering code .P (e.g. SUHP 2/28WH.P)
- Tamper resistant screws available on request Suffix ordering code /TR (e.g. SUHP 2/28WH/TR)
- Opal lens available on request

Material:

- Body: polycarbonate
- Lens: polycarbonate

Finish:

- Body: white, black
- Lens: prismatic



Hawk

Lamp type (Supplied)	Ordering Code	
	White	Black
1 x 28w TC-DD (GR10q)	SUHP 2/28WH	SUHP 2/28B
1 x 28w TC-DD (GR10q)	E3-SUHP 2/28WH	E3-SUHP 2/28B



These luminaires are designed to comply with EN 60598-1 (BS 4533:101) Emergency EN 60598.2.22 (BS 4533:102.22)

