

Kestrel

Universal Surface Ceiling Luminaires

Kestrel, IP65 low energy compact fluorescent wall or ceiling luminaire, for interior or exterior use. Features durable polycarbonate lens and die-cast aluminium body. Ideal applications include toilets, corridors, stairways & passageways etc.



Prismatic lens

Features:

- IP65 (dust tight & water jet proof)
- Low energy compact fluorescent light source
- High Frequency (HF) control gear ●●
- Wall or ceiling mounting
- Screw on lens
- Removable gear tray
- 4 x 20mm conduit entry for side wiring

Options:


- Integral 3hr. maintained emergency (E3) ●●
- Integral D-tect occupancy/light sensor (see data sheet M3/102) ●●●●
- 5w TC-SE Courtesy Light (CRT) separately switched version available
Suffix ordering code /CRT (e.g. SUKP 2/28CRT)
- Opal lens available on request

Material:

- Body: die-cast aluminium
- Lens: polycarbonate

Finish:


- Body: white
- Lens: prismatic



Conduit entry



5w TC-SE Courtesy Light (CRT) with D-tect



Kestrel

Ordering Code

Lamp type (Not supplied)

High Frequency (HF) Emergency (E3)
(integral gear)

1 x 28w TC-DD (GR10q)

SUKP 2/28

E3-SUKP 2/28

1 x 38w TC-DD (GR10q)

SUKP 2/38

E3-SUKP 2/38



These luminaires are designed to comply with
EN 60598-1 (BS 4533:101)
Emergency EN 60598.2.22 (BS 4533:102.22)

