

Exterior Buried LED Uplighters

Cube, IP67 miniature collection of recessed luminaires. Features compact, high output, energy efficient LED light sources (1w LED (350mA) or 3w LED (700mA)). Ideal for use in prestigious interior or exterior areas.



Features:

- IP67 (dust tight & temporary water immersion)
- High Output LED light source (1 x 1/3w 350mA/700mA)
- High Output RGB LED light source (1 x 3w 350mA)
- Low power consumption (energy efficient)
- Low surface temperatures
- Precision heatsink allows for advanced thermal management
- Recessed mounting
- Easy to install via retaining clips
- Contemporary design
- To be used in conjunction with external driver unit (see data sheet X3/104)

Options:


- Warm white, natural white, cool white, blue, amber, red, green, RGB LEDs
- Symmetrical 25°, 40° or 120° beam angles
- Recessing housing for walls/floors/ceilings
- Recessing housing for buried mounting
- Recessing housing for buried mounting (IP67)

Material:

- Body: aluminium or stainless steel AISI 316
- Lens: glass

Finish:

- Body: chrome, anodized, polished or satin
- Lens: clear or satin



Cube

| Lamp type (Supplied) | Beam | Ordering Code | | | |
|--|------|--------------------|----------------------|----------------------------|-------------------------|
| | | Chrome (aluminium) | Anodized (aluminium) | Polished (stainless steel) | Satin (stainless steel) |
| Clear lens | | | | | |
| 1 x 1/3w LED (350mA/700mA) | 25° | MS L00500† | MS L00502† | MS L00504† | MS L00506† |
| 1 x 1/3w LED (350mA/700mA) | 40° | MS L00508† | MS L00510† | MS L00512† | MS L00514† |
| 1 x 1/3w LED (350mA/700mA) | 120° | MS L00516† | MS L00518† | MS L00520† | MS L00522† |
| Satin lens | | | | | |
| 1 x 1/3w LED (350mA/700mA) | 120° | MS L00517† | MS L00519† | MS L00521† | MS L00523† |
| Accessories | | | | | |
| Recessing housing for walls/floors/ceilings | | | | MS L00567 | |
| Recessing housing for buried mounting | | | | MS L00465 | |
| Recessing housing for buried mounting (IP67) | | | | MS L00466 | |

† Suffix LED colour code: 01 - warm white, 02 - natural white, 03 - cool white, 04 - RGB, 05 - blue, 06 - red, 07 - amber, 08 - green (e.g. MS L0041501)



These luminaires are designed to comply with EN 60598-1 (BS 4533:101)

